

Super Class
HD 10/25-4 S

KÄRCHER

Upright cold water high-pressure cleaner. Servopress for adjustment of pressure and water flow rate directly on the trigger gun, pressure switch control, Easy-Press trigger gun with soft grip surface, pivoting stainless steel spray lance, detergent tank, separate compartment for nozzles.

Equipment:

- Spray gun Easy Press trigger gun
- Trigger gun with soft grip insert
- Pressure hose 10 m
- Spray lance 1050 mm
- Triple nozzle (0°/25°/40°) touchless
- Anti-twist system
- 4-pole three-phase motor with air and water cooling
- Pressure cut-off
- Large fine mesh water filter
- Electronic motor protection system with LED display
- Oil sight glass
- Servo Control
- Brass water inlet fitting



Order no.: 1.286-120.0

Technical data

| | |
|-----------------------------------|--------------|
| Supply voltage Ph/V/Hz | 3/400/50 |
| Flow rate (l/h) | 500-1000 |
| Working pressure (bar/MPa) | 30-250/3-25 |
| Max. pressure (bar/MPa) | 275/27.5 |
| Max. water inlet temperature (°C) | up to 60 |
| Connection load (kW) | 9.2 |
| Weight (kg) | 62 |
| Dimensions (L x W x H) (mm) | 560x500x1090 |
| Detergent tank (l) | 6 |

Details

Description

The three-phase HD 10/25-4 S cold water high-pressure cleaner is user friendly and offers an operating pressure of 250 bar at a maximum throughput rate of 1000 l/h.

Thanks to its upright construction, the HD 10/25-4 S takes up less space than a conventional machine and is much easier to manoeuvre, especially up and down steps and stairs. Its large diameter, rubber-tired wheels ensure maximum mobility even in difficult terrain. The push handle adjusts to the most comfortable height for the user. Accessories that are not in use can be kept safely in a separate nozzle compartment.

The easy-press trigger gun offers a high degree of user comfort since it requires less effort to hold and operate and features a servopress controller for convenient adjustment of pressure and water flow rate. The spray lance can be pivoted through 360° while operating at full pressure. Other features are the pressure switch control, which turns off the pump as soon as the trigger is released and thus extends the service life of the motor and pump, and the electronic monitoring system for the motor and pump unit. The built-in detergent tank has a capacity of 6 litres.

The HD 10/25-4 S has been designed for tough daily operating conditions. The chemical-resistant brass cylinder head and ceramic pistons are combined with an efficient air-water cooling system to guarantee a long service life.

Features & Benefits

Proven Kärcher quality

Four-pole, water-cooled electro motor.

Robust brass cylinder head and ceramic piston.

Reinforced, break-resistant plastic chassis.

Hose storage

Mounted on both sides; for 20 m high-pressure hose.

Hose guide under the device; high safety against tilting.

For convenient and fast attachment/removal.

For increased safety

Switch-off in the case of over voltage or low voltage range.

Integrated electronics system for machine monitoring.

Switch-off in the case of leaks or phase failure.

Outstanding mobility

Large rubberised wheels for uneven surfaces, stairs and half landings.

Tried-and-tested sack truck principle for easy, ergonomic transport.

Accessories

Adapter for variable pressure spray lance

Adapter for variable pressure lance

For items 4.760-230 and 4.760-362 for mounting accessories to lance, M 24/18 x 1.5

Order no. 4.762-075.0



Adapters

Adapter M 22 – Swivel

M22 x 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection.

Order no. 4.424-004.0



Angled vario nozzle 0-90°

Variable angle nozzle 0–90°

Variable angle nozzle for spray angle adjustment from 0° to 90°. For easy adjustment to all kinds of soiling and surfaces.

Order no. 4.763-039.0



Angular spray lance

Spray lance for toilets and rain gutters

Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.

Order no. 4.760-073.0



Automatic, self-winding hose reels

Automatic hose reel, coated

Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.

Order no. 2.639-919.0



Powder-coated swivel holder

Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.

Order no. 2.639-931.0



Automatic hose reel, stainless steel, includes swivel holder

Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.

Order no. 6.391-421.0



Automatic, self-winding hose reels

Automatic hose reel, powder-coated steel / plastic

Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.

Order no. 6.392-975.0



Automatic stainless steel / synthetic material hose drum

Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.

Order no. 6.392-965.0



ABS automatic stainless steel hose drum

High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrosion-resistant, watertight capsuled sprung drive. Connection for HP hoses with nipple.

Order no. 2.641-866.0



ABS pivoting stainless steel wall bracket

Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.

Order no. 2.641-867.0



Backflow check valve

Backflow preventer

To prevent detergent getting into the drinking water cycle in case of inlet at low-pressure. - hot water resistant up to 80 °C - tested according to IEC 60335-2-79 - integrated leakage protection

Order no. 2.641-374.0



Barrel and tank cleaning

Barrel cleaner BC 14/12

The BC 14/12 is an spray system for the efficient interior cleaning of containers and barrels, specially oak barrels with a volume of between 225 and 600 litres. One cleaning cycle is completed within 36 seconds and every spot in the container is covered by a water jet. After cleaning is finished the BC 14/12 can easily and conveniently take up the dirty water. The transformer included with the BC 14/12 makes it possible to use it worldwide (110 - 240 V, 50 - 60 Hz). The nozzle kits included make possible use with high-pressure cleaners with a water volume of 600 to 1400 l / h. Electrical components are protected in accordance with IP 55.

Order no. 2.641-740.0



Boron carbide nozzle

Boron carbide nozzle, for machines up to 1,000 l/h

In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.

Order no. 6.415-084.0



Cleaning agent injector

Cleaning agent injector for high pressure (without nozzle)

Cleaning agent dosage at high pressure 3 - 5 %

Order no. 3.637-170.0



Cleaning agent injector for high and low pressure (without nozzles)

Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.

Order no. 3.637-001.0



Connector

Nozzle screws / screw socket

Nozzle connector/screw connector for connecting high-pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: 1x M 22 x 1.5 and 1x M 18 x 1.5.

Order no. 4.402-022.0



Coupling

Coupling

Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: 2x M 22 x 1.5 m.

Order no. 4.403-002.0



Crane lifting kit

Crane loading kit for HD super class

Effortless loading by crane.

Order no. 2.640-438.0



Cup foam lance

Cup foam lance

Short, handy foam lance with adjustable spray angle with 1 litre detergent tank. Ideal for cleaning cars due to its compact design.

Order no. 6.394-668.0



Cup foam lance

1-litre cleaning agent container for foam lance

Order no. 6.414-954.0



Dirt blaster, large

Dirt blaster

The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.

Order no. 4.763-253.0



Double lance

Double lance 960 mm

960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).

Order no. 6.394-665.0



Easy Foam Set

Easy Foam Set with RM injector

HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.

Order no. 2.640-691.0



Easy Press high-pressure trigger gun with holding force reduction (Kärcher patent)

Easy Press HP trigger gun with soft grip

Easy press high-pressure trigger gun with softgrip. For high-pressure hoses DN 6 and DN 8 with 11 mm swivel diameter.

Order no. 4.775-463.0



Flexible spray lance

Flexible lance 1050 mm

1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.

Order no. 6.394-654.0



Foam nozzle mounting kit

Foam nozzle attachment kit

Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.



Order no. 2.637-926.0

Food industry version

High-pressure hose, 10 m, DN 8, AVS trigger gun connection, food, grey

Food industry version, AVS connection in the trigger gun. grey NW 8/155 °C/250 bar



Order no. 6.390-704.0

High-pressure hose, 20 m, ID 8, AVS trigger gun connector, suitable for food industry, grey

20 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. NW 8/155°C/250 bar.



Order no. 6.390-705.0

Food industry version with unions on both sides

High-pressure hose, 10 m, DN 8, suitable for the food industry, extension piece

10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M 22 x 1.5 with anti-kink sleeve.



Order no. 6.389-479.0

High-pressure hose, 20 m, ID 8, suitable for food industry, extension piece

20 m high-pressure hose (DN 8) with swivel coupling. Non-discolouring outer layer for use in the food industry. Connectors at both ends, M 22 x 1.5, with kink protection. NW 8/155°C/250 bar.



Order no. 6.389-581.0

FR 30 Me surface cleaner

Hard surface cleaner FR 30 Me

Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.

Order no. 2.640-355.0



FRV 30 Me surface cleaner

FRV 30 Me

Order no. 2.642-911.0



FRV 30 Me surface cleaner

FRV 30 Me extension hose

Order no. 4.441-040.0



Geka coupling

Geka connector with hose barb, R 3/4"

with hose liner

Order no. 6.388-455.0



Geka connector with inner thread, R 1"

with female thread

Order no. 6.388-458.0



Grey wheel kit

Non-marking grey wheel attachment kit

Grey wheels that do not leave streaks for cleaning in the sanitary or food industries or swimming pools.

Order no. 2.641-493.0



Gutter cleaner

Gutter cleaning lance

The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.

Order no. 2.642-305.0



Hard surface cleaner FR 50

Hard surface cleaner FR 50

Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas. With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system.

Order no. 2.640-679.0



Hard surface cleaner FRV 30

FRV 30 surface cleaner

Order no. 2.642-999.0



Rubber lip for FRV 30

For smooth floors indoors. The squeegee increases the suction performance of the FRV 30 and minimises the amount of water remaining. This means the floor is dry in just a few minutes.



Order no. 2.642-910.0

Extension hose 5 m

5m extension hose for FRV 30. Connection sleeve included.

Order no. 4.440-939.0



ABS hose fastening

Order no. 2.642-528.0



ABS dirt trap

Order no. 2.642-532.0



HKF 50 spray head, brass

HKF 50 spray head, brass

Depth of immersion 850 mm. Interior cleaning head for barrels and containers with bungholes of 50 mm and more. Can be directly connected to the high-pressure cleaner. Electric motor drive. Operation is possible both vertically and horizontally



Order no. 3.631-039.0

Inaktiv

High-pressure hose Longlife 400, 10 m DN 8, AVS trigger gun connection

Order no. 6.389-856.0



Spray lance, 2,050 mm, swivelling, ergonomical

Spray lance, 2,050 mm, swivelling, ergonomical

Order no. 4.760-366.0



Rotary coupling

Order no. 4.401-076.0



Inno Foam Kit

Inno Foam Set with detergent injector

High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.

Order no. 2.640-151.0



iSolar brushes and water softening

iSolar 400

iSolar 400 brush for water flow rate of 700-1,000 l/h. The water-driven disc brush with a width of 400 mm cleans small to medium-sized photovoltaic systems. Also perfect for use on elevated systems.

Order no. 6.368-456.0



iSolar 800

iSolar 800 water-driven brush head, 800 mm wide, for water flow rates of 700-1,000 l/h. With two contra-rotating disc brushes and flexible angle joint. For photovoltaic systems.

Order no. 6.368-454.0



iSolar brushes and water softening

iSolar fall protection

Certified personal security system for rooftop work. Contents: Travelling fall arrestor with shock absorber and 15 m kernmantle rope, harness, anchoring sling and sheet steel case.

Order no. 6.988-152.0



WS 50

Order no. 6.368-463.0



WS 100

Order no. 6.368-464.0



WS Regenerator

Order no. 6.368-465.0



Longlife 400

High-pressure hose Longlife 400, 20 m, DN 8, AVS trigger gun connector

20 m high-pressure hose Longlife 400 (DN 8) with patented (rotating) AVS trigger gun connector and manual coupling. Two layer high-strength steel wire reinforced.

Order no. 6.390-208.0



Longlife 400 high-pressure hose, 10 m, DN 8,

Order no. 6.391-351.0



Longlife 400 with unions on both sides

High-pressure hose 1.5 m, ID 8, including connectors

1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 x 1.5).

Order no. 6.390-178.0



High-pressure hose Longlife 400, 10 m, ID 8, including rotary coupling

10 m high-pressure hose Longlife 400 (DN 8) with rotary coupling, two layer high-strength steel wire reinforced. Connectors at both ends. M 22 x 1.5, with kink protection.

Order no. 6.388-083.0



High-pressure hose Longlife 400, 20 m, ID 8, extension

with rotary coupling, 2 x M 22 x 1.5

Order no. 6.390-027.0



Longlife 400 high-pressure hose, 10 m, DN 8, extension piece

Order no. 6.391-354.0



High-pressure hose Longlife 400, 15 m, ID 8, including rotary coupling

With rotary coupling, 2 x M 22 x 1.5

Order no. 6.389-709.0



High-pressure hose Longlife 400, 30 m, ID 8, including rotary coupling

With rotary coupling, 2 x M 22 x 1.5

Order no. 6.390-294.0



Longlife food design

High-pressure hose Longlife 400, 10 m, ID 8, AVS trigger gun connection

Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With patented AVS connection in the pistol (pivot mounted)

Order no. 6.391-885.0



Longlife food design

High-pressure hose Longlife 400, 20 m, ID 8, AVS trigger gun connection

Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With patented AVS connection in the pistol (pivot mounted)

Order no. 6.391-886.0



Longlife food design with screw connections at both ends

High pressure hose food ID 8, 10 m

Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With rotary coupling, 2 x M 22 x 1,5

Order no. 6.391-864.0



High-pressure hose food industry 400 bar, 20 m, ID 8, including rotary coupling

Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With rotary coupling, 2 x M 22 x 1,5

Order no. 6.391-887.0



Machine-specific nozzle kit with order no. 3.637-170.0

Nozzle kit 750-1000 l/h

For HD/HDS 750 - 1000 l/h. Consists of nozzle insert + HP power nozzle + union

Order no. 4.769-047.0



Machine-specific nozzle kits for FR

Nozzle kit for surface cleaners

Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (850 to 1100 l/h).

Order no. 2.640-442.0



Machine-specific nozzle kits for FRV

Nozzle kit 050 – for FRV 30

Order no. 2.642-433.0



Manual hose reel attachment kit

Hose reel kit for HD super class

ABS hose reel for mounting on the machine. For safe and tidy stowage of high-pressure hoses (with connecting hose to machine's HP outlet) Can be rotated under pressure, with M 22 x 1.5 connection.

Order no. 2.640-439.0



Nozzle insert with order no. 3.637-001.0

Nozzle insert up to 1,100 l/h - high pressure

Nozzle insert for detergent injector 3.637-001 for high-pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.

Order no. 4.769-003.0



Nozzle insert up to 1,100 l/h - low pressure

For low pressure with machines up to 1.100 l/h

Order no. 4.769-001.0



Nozzle kit for spray head HKF 50 (3.631-009.0 / 3.631-039.0)

Nozzle 045 for 2-nozzle operation HKF 50

Nozzle for dual-nozzle operation

Order no. 6.415-446.0



Nozzle 090 for 1-nozzle operation HKF 50

Nozzle for single-nozzle operation

Order no. 6.415-447.0



Cone for plugging into bungholes

Cone for plugging into bungholes

Order no. 4.132-002.0



Double grip for precise control of spray head

Double handle. Precise control of the spray head

Order no. 2.863-036.0



Screw plug for using a spray head with one nozzle

Screw plug for using a spray head with one nozzle

Order no. 5.411-061.0



Nozzle kits for Inno/Easy Foam Set

Nozzle kit 090 for Inno / Easy Set 700–1,000 l/h

Nozzle kit contains Kärcher power nozzles and nozzle inserts. For Inno/Easy-Foam set 700-1000 l/h. For optimal foam system performance.

Order no. 2.640-688.0



Nozzle kits for wet jet unit

Nozzle kit for wet jet unit 050

Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachment 4.762-010/-022.

Order no. 2.637-902.0



Nozzle union

Nozzle connector

For protecting and connecting Kärcher power nozzles to spray lances (M 18 x 1.5 IG).

Order no. 5.401-210.0



Pipe cleaning hose, ID 6

Pipe cleaning hose, DN 6, 20 m, max. 250 bar

The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).

Order no. 6.390-030.0



Pipe cleaning nozzle

Pipe cleaning dirt blaster D 25 / 060

The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the necessary forward movement, as well as convenient handling.

Order no. 6.415-945.0



Pipe cleaning dirt blaster D 30 / 060

The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the necessary forward movement, as well as convenient handling.

Order no. 6.415-947.0



Pipe cleaning dirt blaster D 35 / 060

The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the necessary forward movement, as well as convenient handling.

Order no. 6.415-949.0



Pipe cleaning nozzle

Pipe cleaning nozzle 100

Pipe cleaning nozzle with 24 mm diameter. With 4 nozzles tilted back at a 30° angle.

Order no. 5.763-088.0



Pipe cleaning nozzle 120

Pipe cleaning nozzle with 24 mm diameter. With 8 nozzles tilted back at a 30° angle.

Order no. 5.763-089.0



Pipe cleaning nozzle

16 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.

Order no. 5.763-019.0



Pipe cleaning nozzle

16 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.

Order no. 5.763-020.0



Pipe cleaning nozzle

30 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.

Order no. 5.763-021.0



Rotating pipe cleaning nozzle

Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blocked drains and pipes.

Order no. 6.415-440.0



Power nozzle spray angle 25°

25° power nozzle for cleaning agent suction

Order no. 2.884-521.0



Push-on washing brush

Push-on washing brush

Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 x 1.6.

Order no. 4.762-016.0



Quick connect

Quick coupling

For quick change of different spray lances and accessories. Optimum adaption to Kärcher accessories, especially for connection between trigger gun and spray lance. With M22 x 1,5 female.

Order no. 6.401-458.0



Male coupling

Hardened stainless steel nipple for quick coupling 6.401-458. With M22 x 1,5 male.

Order no. 6.401-459.0



Rollover nozzle holder

Rollover nozzle holder

Rollover nozzle holder for contactless changeover from pencil jet to fan jet as well as low-pressure detergent injection via knurled nut. Without nozzle insert. (Additional type-specific power nozzle).

Order no. 4.764-012.0



Rotary coupling

Rotary coupling

Kärcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector M 22 x 1.5 m. With grip protection.

Order no. 4.401-091.0



Rotating spray lances

1050 mm spray pipe, rotatable

1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.

Order no. 4.760-660.0



600 mm spray pipe, rotatable

600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.

Order no. 4.760-664.0



Rotating spray lances

850 mm spray pipe, rotatable

850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.

Order no. 4.760-663.0



1550 mm spray pipe, rotatable

1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.

Order no. 4.760-661.0



2050 mm spray pipe, rotatable

2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.

Order no. 4.760-662.0



Rotating washing brush

Rotating washing brush for > 800 l/h machines

Order no. 4.762-559.0



Rotating washing brush for > 800 l/h machines

Order no. 4.762-562.0



Servo control

Servo control

Order no. 4.775-470.0



Solar cleaning – telescopic lances

iSolar TL 7 H (without hose)

Telescopic rod made from a carbon/fibreglass mixture for maximum rigidity with minimum weight. With 7.2 m max. reach and practical quick-release couplings for easy extension and retraction.

Order no. 4.107-054.0



Solar cleaning – telescopic lances

iSolar TL 10 H (without hose)

Telescopic rod made from a carbon/fibreglass mixture for maximum rigidity with minimum weight. With 10 m max. reach and practical quick-release couplings for easy extension and retraction.

Order no. 4.107-053.0



iSolar TL 10 C (without hose)

Order no. 4.107-055.0



iSolar TL 14 C (without hose)

Full carbon telescopic rod for maximum rigidity with minimal weight. With 14 m max. reach and practical quick-release couplings for easy extension and retraction.

Order no. 4.107-052.0



iSolar HP hose 7

High-quality, flexible HP hose (with rubber covering) for the iSolar TL 7. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.

Order no. 6.392-978.0



iSolar HP hose 10

High-quality, flexible HP hose (with rubber covering) for the iSolar TL 10. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.

Order no. 6.392-977.0



iSolar HP hose 14

High-quality, flexible HP hose (with rubber covering) for the iSolar TL 14. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.

Order no. 6.392-976.0



Spacer (including nozzle union)

Spacer (includes nozzle screws)

Guarantees constant safety clearance, e.g. for tyres and bodywork. Helps prevent damage to sensitive surfaces. Mounts directly to lance.

Order no. 5.394-294.0



Special hoses

High-pressure hose 1.5 m, ID 8, including connectors, outlet bend

Order no. 6.388-886.0



Spray lance

250 mm lance, non-rotatable

250 mm stainless steel lance. With manual coupling. Non-rotatable.

Order no. 4.760-667.0



Spray lances

Vibrasoft lance

The spring-loaded 360° loop handle significantly reduces the vibrations on the spray lance, reducing the physical burden on the user, e.g. when working with the dirt blaster.

Order no. 6.415-951.0



Standard

High-pressure hose, 10 m, ID 8, AVS trigger gun connector

10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.

Order no. 6.390-025.0



High-pressure hose, 15 m, ID 8, AVS trigger gun connector

15 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.

Order no. 6.390-185.0



High-pressure hose, 20 m, ID 8, AVS trigger gun connector

20 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.

Order no. 6.390-171.0



Standard with unions on both sides

High-pressure hose, 15 m, ID 8, 315 bar, including rotary coupling

Order no. 6.390-010.0



High-pressure hose, 20 m, ID 8, 315 bar, extension piece

Order no. 6.390-031.0



High-pressure hose, 15 m, ID 10, 220 bar, extension piece

Order no. 6.390-023.0



High-pressure hose, 10 m, ID 8, 315 bar, extension piece

Order no. 6.391-342.0



High-pressure hose, 30 m, ID 8, including rotary coupling

Order no. 6.390-293.0



Suction filter

Suction filter with check valve

Brass suction filter suitable for ponds, storage tanks, etc. With check valve.

Order no. 4.730-012.0



Water suction filter

Order no. 6.414-956.0



Telescopic spray lance

Telescopic spray lance

Order no. 6.394-690.0



Telescopic spray lance

Strap for telescopic spray pipe

Convenient strap for relief when working with the telescopic spray lance (6.394-690). The burden is optimally distributed on the body and longer periods of use are possible.

Order no. 6.373-987.0



Trigger guns

High-end HP trigger gun

Order no. 4.775-823.0



Triple nozzle, touchless changeover

Triple nozzle, touchless changeover

Triple nozzle with high-pressure pencil jet (25°) and low-pressure fan jet (40°). Fast and easy jet changeover by turning the nozzle.

Order no. 4.767-065.0



Triple nozzles

Triple nozzle 050

Triple nozzle with manual nozzle changeover. Convenient spray adjustment. For high-pressure cleaners with injector; low-pressure fan jet for detergent removal and application. Connector M 18x1.5.

Order no. 4.767-154.0



Undercarriage spray lance

Underbody lance

Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.

Order no. 4.760-245.0



Variable pressure spray lance

Variable pressure spray lance

670 mm variable pressure lance with integrated pressure gauge. Variable pressure adjustment on the handle. Nozzle connector: M 24 x 1.5. Low pressure detergent application.

Order no. 4.760-362.0



Variable pressure lance

1040 mm pressure adjustable lance with integrated pressure gauge. Variable pressure adjustment on the handle. Nozzle connector: M 24 x 1.5. Low pressure detergent application.

Order no. 4.760-230.0



Water fine filter

Water fine filter, with adapter

Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1".

Order no. 4.730-102.0



Water fine filter, 100 µm, R 1"

Fine-mesh water filter, 100 µm, max. temperature 60°C. Connects to high-pressure cleaner. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connector 1".

Order no. 2.638-270.0



Water supply hose

Water supply hose

NW 19 R1" / R 3/4", up to 85 °C, for pick-up

Order no. 4.440-207.0



Water supply hose

NW 19 R1" / R1", up to 85 °C

Order no. 4.440-270.0



Wet blasting attachment (without nozzle)

Wet blasting attachment with flow control (without nozzles)

Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.

Order no. 4.762-010.0



Wet blasting attachment without flow control (nozzles not included)

Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.

Order no. 4.762-022.0



Y distributor

Y distributor

Order no. 4.405-048.0

