



## HDS 6/14 CX

Single-phase HDS 6/14 CX hot water high-pressure cleaner with eco!efficiency mode, Easy Press trigger gun, Servo Control and in-built hose reel - including a 15-metre pressure hose.



### 1 Efficiency

- eco!efficiency mode - economical and environmentally friendly, even during longer periods of use.
- Reduces fuel consumption and CO2 emissions by 20%.

### 2 Ease of use

- Intuitive operation with large single-button selector switch.
- Large tank opening with filling chute.

### 3 Storage

- Lockable accessory compartment for nozzles, tools, etc.
- Integrated hose reel with 15 m pressure hose. For a large operating radius and effortless stowage (CX variants).

### 4 Reliability

- The Soft Damping System (SDS) compensates for vibration and pressure peaks in the high-pressure system.
- Large water filter protects pump against damage.



## HDS 6/14 CX

- Economical ecoefficiency mode
- Intuitive single-button selector switch
- Extensive range of standard equipment

### Technical data

<b>Order No.</b>	1.169-220.0	
<b>EAN code</b>	4039784717336	
<b>Supply voltage</b>	<b>Ph / V / Hz</b>	1 / 230 / 50
<b>Flow rate</b>	<b>l/h</b>	240-560
<b>Pressure</b>	<b>bar / MPa</b>	30-140 / 3-14
<b>Max. temperature</b>	<b>°C</b>	80 / 155
<b>Connection load</b>	<b>kW</b>	3.6
<b>Heating oil or gas consumption, full load</b>	<b>kg/h</b>	3.5
<b>Fuel tank</b>	<b>l</b>	15
<b>Weight</b>	<b>kg</b>	95
<b>Dimensions (L × W × H)</b>	<b>mm</b>	1215 × 650 × 920
<b>Cleaning agent tank</b>	<b>l</b>	10

### Equipment

<b>Spray gun</b>	Easy Press trigger gun	
<b>Spray gun with soft grip</b>	■	
<b>Pressure hose</b>	<b>m</b>	15 / DN 6, 250 bar
<b>Spray lance</b>	<b>mm</b>	1050
<b>Power nozzle</b>	■	
<b>Soft Damping System (SDS)</b>	■	
<b>Integrated pressure hose reel</b>	■	
<b>Anti-twist system</b>	■	
<b>Pressure cut-off</b>	■	
<b>Integrated fuel and cleaning agent tank</b>	■	
<b>Servo Control</b>	■	

■ Included in delivery.

# ACCESSORIES FOR HDS 6/14 CX

## 1.169-220.0

**KÄRCHER**



		Order No.	ID	Max. working pressure	Length	Price	Description	
<b>Standard with unions on both sides</b>								
High-pressure hose, 10 m, ID 8, 315 bar, extension piece	1	6.391-342.0	DN 8	315 bar	10 m			▲
High-pressure hose, 30 m, ID 8, including rotary coupling	2	6.390-293.0	DN 8	315 bar	30 m			▲
<b>Longlife 400 with unions on both sides</b>								
High pressure hose ID 6, 10 m, including rotary coupling	3	6.391-883.0	DN 6	400 bar	10 m		With rotary coupling, 2 x M 22 x 1.5	▲
Longlife 400 high-pressure hose, 10 m, DN 8, extension piece	4	6.391-354.0	DN 8	400 bar	10 m			▲
High-pressure hose Longlife 400, 30 m, ID 8, including rotary coupling	5	6.390-294.0	DN 8	400 bar	30 m		With rotary coupling, 2 x M 22 x 1.5	▲
High-pressure hose 1.5 m, ID 8, including connectors	6	6.390-178.0	DN 8	400 bar	1.5 m		1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 x 1.5).	□
<b>Longlife food design with screw connections at both ends</b>								
High pressure hose food ID 8, 10 m	7	6.391-864.0	DN 8	400 bar	10 m		Longlife HP hose for use in the food industry. Außen-decke## animal-grease-resistant, non-colour-bleeding material. With rotary coupling, 2 x M 22 x 1.5	▲
High-pressure hose food industry 400 bar, 20 m, ID 8, including rotary coupling	8	6.391-887.0	DN 8	400 bar	20 m			▲
<b>Standard</b>								
High-pressure hose, 15 m, ID 6, AVS gun connection	9	6.391-394.0	DN 6	250 bar	15 m			■
High-pressure hose, 10 m, ID 6, 300 bar, AVS trigger gun connection	10	6.391-875.0	DN 6	300 bar	10 m		With patented AVS connection in the trigger gun (pivot-mounted) and hand screw union. M 22 x 1.5 with anti-kink protection. NW 6/155°C/300 bar	□
High-pressure hose, 10 m, ID 8, AVS trigger gun connector	11	6.390-025.0	DN 8	315 bar	10 m		10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.	□
High-pressure hose, 15 m, ID 8, AVS trigger gun connector	12	6.390-185.0	DN 8	315 bar	15 m		15 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.	□
High-pressure hose, 20 m, ID 8, AVS trigger gun connector	13	6.390-171.0	DN 8	315 bar	20 m		20 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.	□
<b>Longlife 400</b>								
Longlife 400 high-pressure hose, 10 m, DN 6, M 22 x 1.5	14	6.391-882.0	DN 6	400 bar	10 m		With patented AVS connection in the trigger gun (pivot-mounted).	□
Longlife 400 high-pressure hose, 10 m, DN 8,	15	6.391-351.0	DN 8	400 bar	10 m			□
High-pressure hose Longlife 400, 20 m, DN 8, AVS trigger gun connector	16	6.390-208.0	DN 8	400 bar	20 m		20 m high-pressure hose Longlife 400 (DN 8) with patented (rotating) AVS trigger gun connector and manual coupling. Two layer high-strength steel wire reinforced.	□
<b>Food industry version</b>								
High-pressure hose, 15 m, ID 6, AVS trigger gun connector 11 mm, suitable for food industry, grey	17	6.391-654.0	DN 6	250 bar	15 m		15 m high-pressure hose (DN 6) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. DN 6/155°C/250 bar.	□
High-pressure hose, 10 m, DN 8, AVS trigger gun connection, food, grey	18	6.390-704.0	DN 8	250 bar	10 m		Food industry version, AVS connection in the trigger gun. grey NW 8/155 °C/250 bar	□

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# ACCESSORIES FOR HDS 6/14 CX

## 1.169-220.0




		<b>Order No.</b>	<b>ID</b>	<b>Max. working pressure</b>	<b>Length</b>		<b>Price</b>	<b>Description</b>	
High-pressure hose, 20 m, ID 8, AVS trigger gun connector, suitable for food industry, grey	19	6.390-705.0	DN 8	250 bar	20 m			20 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. NW 8/155°C/250 bar.	<input type="checkbox"/>
<b>Longlife food design</b>									
High-pressure hose Longlife 400, 15 m, ID 6, AVS trigger gun connection	20	6.391-888.0	DN 6	400 bar	15 m			Longlife HP hose for use in the food industry. Außen-decke## animal-grease-resistant, non-colour-bleeding material. With patented AVS connection in the pistol (pivot mounted)	<input type="checkbox"/>
High-pressure hose Longlife 400, 10 m, ID 8, AVS trigger gun connection	21	6.391-885.0	DN 8	400 bar	10 m				<input type="checkbox"/>
High-pressure hose Longlife 400, 20 m, ID 8, AVS trigger gun connection	22	6.391-886.0	DN 8	400 bar	20 m				<input type="checkbox"/>
<b>Special hoses</b>									
High-pressure hose 1.5 m, ID 8, including connectors, outlet bend	23	6.388-886.0	DN 8	400 bar	1.5 m				<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.



# ACCESSORIES FOR HDS 6/14 CX

## 1.169-220.0



		Order No.	Nozzle size					Price	Description	
<b>Power nozzle spray angle 25°</b>										
Power nozzle spray angle 25°	1	2.883-821.0	36						Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains.	■
25° power nozzle for cleaning agent suction	2	2.884-521.0	250							□
<b>HP nozzle spray angle 0°</b>										
High-pressure nozzle spray angle 0°	3	2.884-533.0	40						High-pressure nozzle with powerful jet for extremely stubborn dirt.	□
<b>Power nozzle spray angle 15°</b>										
Power nozzle spray angle 15°	4	2.885-225.0	36							□
<b>Power nozzle spray angle 40°</b>										
Power nozzle spray angle 40°	5	2.884-522.0	40						Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.	□

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# ACCESSORIES FOR HDS 6/14 CX

## 1.169-220.0

**KÄRCHER**



		Order No.	Max. working pressure	Length		Price	Description	
<b>Rotating spray lances</b>								
1050 mm spray pipe, rotatable	1	4.760-660.0	300 bar	1050 mm			1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	■
600 mm spray pipe, rotatable	2	4.760-664.0	300 bar	600 mm			600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	□
850 mm spray pipe, rotatable	3	4.760-663.0	300 bar	840 mm			850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	□
1550 mm spray pipe, rotatable	4	4.760-661.0	300 bar	1550 mm			1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	□
2050 mm spray pipe, rotatable	5	4.760-662.0	300 bar	2050 mm			2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	□
<b>Spray lances</b>								
Vibrasoft lance	6	6.415-951.0	250 bar	950 mm			The spring-loaded 360° loop handle significantly reduces the vibrations on the spray lance, reducing the physical burden on the user, e.g. when working with the dirt blaster.	□
<b>Spray lance</b>								
250 mm lance, non-rotatable	7	4.760-667.0		250 mm			250 mm stainless steel lance. With manual coupling. Non-rotatable.	□
<b>Double lance</b>								
Double lance 960 mm	8	6.394-665.0	310 bar	960 mm			960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use ( e.g. stable cleaning).	□
<b>Variable pressure spray lance</b>								
Variable pressure spray lance, 280 mm.	9	4.760-387.0		280 mm			With integral pressure gauge for infinitely variable pressure control directly on lance. Nozzle connection M 24 x 1.5. Chemical feed in low pressure mode. Variable pressure lance and Kärcher Power nozzle.	□
Variable pressure spray lance	10	4.760-362.0		670 mm			670 mm variable pressure lance with integrated pressure gauge. Variable pressure adjustment on the handle. Nozzle connector: M 24 x 1.5. Low pressure detergent application.	□
Variable pressure lance	11	4.760-230.0		1040 mm			1040 mm pressure adjustable lance with integrated pressure gauge. Variable pressure adjustment on the handle. Nozzle connector: M 24 x 1.5. Low pressure detergent application.	□
<b>Adapter for variable pressure spray lance</b>								
Adapter for variable pressure lance	12	4.762-075.0					For items 4.760-230 and 4.760-362 for mounting accessories to lance, M 24/18 x 1.5	□
<b>Angular spray lance</b>								
Spray lance for toilets and rain gutters	13	4.760-073.0					Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.	□
<b>Flexible spray lance</b>								
Flexible lance 1050 mm	14	6.394-654.0	210 bar	1050 mm			1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.	□
<b>Telescopic spray lance</b>								
Telescopic spray lance	15	6.394-690.0	225 bar					□

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# ACCESSORIES FOR HDS 6/14 CX

## 1.169-220.0



		Order No.	Max. working pressure	Length		Price	Description	
Strap for telescopic spray pipe	16	6.373-987.0					Convenient strap for relief when working with the telescopic spray lance (6.394-690). The burden is optimally distributed on the body and longer periods of use are possible.	<input type="checkbox"/>
<b>Gutter cleaner</b>								
Gutter cleaning lance	17	2.642-305.0					The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.	<input type="checkbox"/>
<b>Undercarriage spray lance</b>								
Underbody lance	18	4.760-245.0		700 mm			Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.



# ACCESSORIES FOR HDS 6/14 CX


## 1.169-220.0



		Order No.					Price	Description	
<b>Crane lifting kit</b>									
Crane loading attachment kit for HDS compact class	1	2.642-638.0							<input type="checkbox"/>
<b>Flame monitoring attachment kit</b>									
Flame monitoring attachment kit for HDS compact class	2	2.642-711.0							<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# ACCESSORIES FOR HDS 6/14 CX 1.169-220.0



		Order No.	Flow rate	Nozzle size	Diame- ter	Price	Description	
<b>Hard surface cleaner FRV 30</b>								
FRV 30 surface cleaner	1	2.642-999.0						<input type="checkbox"/>
Rubber lip for FRV 30	2	2.642-910.0					For smooth floors indoors. The squeegee increases the suction performance of the FRV 30 and minimises the amount of water remaining. This means the floor is dry in just a few minutes.	<input type="checkbox"/>
ABS hose fastening	3	2.642-528.0						<input type="checkbox"/>
ABS dirt trap	4	2.642-532.0						<input type="checkbox"/>
<b>Hard surface cleaner FR 30</b>								
FR 30	5	2.642-997.0			300 mm			<input type="checkbox"/>
<b>FR 30 Me surface cleaner</b>								
Hard surface cleaner FR 30 Me	6	2.111-013.0			300 mm		Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.	<input type="checkbox"/>
	7	2.640-355.0			300 mm			<input type="checkbox"/>
	8	2.640-448.0						<input type="checkbox"/>
<b>Machine-specific nozzle kits for FR</b>								
Nozzle kit for surface cleaners	9	2.640-401.0	500-650 l/h				Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (500 to 650 l/h).	<input type="checkbox"/>
<b>Machine-specific nozzle kits for FRV</b>								
Nozzle kit 035 - for FRV 30	10	2.642-430.0		35				<input type="checkbox"/>
<b>FRV 30 Me surface cleaner</b>								
FRV 30 Me	11	2.642-911.0						<input type="checkbox"/>
FRV 30 Me extension hose	12	4.441-040.0						<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# ACCESSORIES FOR HDS 6/14 CX 1.169-220.0



							Order No.				Price	Description	
<b>Nozzle union</b>													
Nozzle connector	1		5.401-210.0									For protecting and connecting Kärcher power nozzles to spray lances (M 18 x 1.5 IG).	<input type="checkbox"/>
Nozzle union food industry	2		5.401-318.0									Made of special brass alloy for use in the food industry.	<input type="checkbox"/>
<b>Spacer (including nozzle union)</b>													
Spacer (includes nozzle screws)	3		5.394-294.0									Guarantees constant safety clearance, e.g. for tyres and bodywork. Helps prevent damage to sensitive surfaces. Mounts directly to lance.	<input type="checkbox"/>
<b>Coupling parts</b>													
Articulated joint	4		6.987-705.0									This articulated joint with variable angle adjustment (up to an angle of 120°) is recommended for cleaning hard to reach areas. Fits directly on the spray lance.	<input type="checkbox"/>
<b>Rotary coupling</b>													
Rotary coupling	5		4.401-091.0									Kärcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector M 22 x 1.5 m. With grip protection.	<input type="checkbox"/>
<b>Coupling</b>													
Coupler -2xM22x1,5	6		4.403-002.0									Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: 2x M 22 x 1.5 m.	<input type="checkbox"/>
<b>Connector</b>													
Nozzle screws / screw socket	7		4.402-022.0									Nozzle connector/screw connector for connecting high-pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: 1x M 22 x 1.5 and 1x M 18 x 1.5.	<input type="checkbox"/>
<b>Adapters</b>													
Adapter M 22 - Swivel	8		4.424-004.0									M22 x 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection.	<input type="checkbox"/>
<b>Flue pipe</b>													
Flue gas adapter	9		4.656-149.0									Flue gas adapter with draught damper for flue pipe connection (adapter for HDS burners for connection to a stack system).	<input type="checkbox"/>
	10		4.656-080.0										<input type="checkbox"/>
<b>Weed control</b>													
WR 50	11		2.643-758.0									In combination with a hot water high-pressure cleaner from Kärcher, the 50-cm-wide WR 50 weed lance is perfect for killing weeds. Supplied with an adaptive chassis and nozzle adaptor.	<input type="checkbox"/>
WR 20	12		2.643-760.0									For thorough weed removal: the WR 20 weed lance for use with a hot water high-pressure cleaner from Kärcher. Equipped with a 20-cm-wide nozzle bar and nozzle adaptor.	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# ACCESSORIES FOR HDS 6/14 CX

## 1.169-220.0




		Order No.	Nozzle size				Price	Description	
<b>Wet blasting attachment (without nozzle)</b>									
Wet blasting attachment with flow control (without nozzles)	1	4.762-010.0						Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.	<input type="checkbox"/>
Wet blasting attachment without flow control (nozzles not included)	2	4.762-022.0						Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.	<input type="checkbox"/>
<b>Nozzle kits for wet jet unit</b>									
Nozzle kit for wet jet unit 040	3	2.637-900.0	40					Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachment 4.762-010/-022.	<input type="checkbox"/>
<b>Boron carbide nozzle</b>									
Boron carbide nozzle, for machines up to 1,000 l/h	4	6.415-084.0	6 mm					In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# ACCESSORIES FOR HDS 6/14 CX

## 1.169-220.0



		Order No.	Max. working pressure	Nozzle size	Diameter		Price	Description	
<b>Pipe cleaning hose, ID 6</b>									
Pipe cleaning hose, DN 6, 20 m, max. 120 bar	1	6.390-028.0	120 bar					The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	<input type="checkbox"/>
Pipe cleaning hose, DN 6, 30 m, max. 120 bar	2	6.390-029.0	120 bar					30 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle).	<input type="checkbox"/>
Pipe cleaning hose, DN 6, 20 m, max. 250 bar	3	6.390-030.0	250 bar					The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	<input type="checkbox"/>
<b>Pipe cleaning nozzle</b>									
Pipe cleaning dirt blaster D 25 / 040	4	6.415-944.0		40	25 mm			The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the necessary forward movement, as well as convenient handling.	<input type="checkbox"/>
Pipe cleaning dirt blaster D 30 / 040	5	6.415-946.0		40	30 mm				<input type="checkbox"/>
Pipe cleaning dirt blaster D 35 / 040	6	6.415-948.0		40	35 mm				<input type="checkbox"/>
Pipe cleaning nozzle	7	5.763-015.0		55	16 mm			16 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.	<input type="checkbox"/>
	8	5.763-016.0		60	16 mm				<input type="checkbox"/>
	9	5.763-017.0		50	30 mm			Pipe cleaning nozzle with inner thread. Different spray directions. The hose moves freely through the pipe. (R 1/8" connection, 3 x 30° backwards, diameter 30 mm.)	<input type="checkbox"/>
Rotating pipe cleaning nozzle	10	6.415-428.0		50	16 mm			Pipe cleaning nozzle with four rotating jets and inner thread. Different spray directions. The hose moves freely through the pipe. With R 1/8" connection.	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# ACCESSORIES FOR HDS 6/14 CX

## 1.169-220.0



		Order No.	Max. working pressure	Nozzle size			Price	Description	
<b>Dirt Blaster, small</b>									
Dirt blaster	1	4.767-023.0	180 bar	40				The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 180 bar, 18 MPa, 60°C.	<input type="checkbox"/>
<b>Dirt blaster, large</b>									
Dirt blaster 04	2	4.763-252.0	300 bar	40				The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.	<input type="checkbox"/>
<b>Inaktiv</b>									
PCH / rotary nozzle 040, cleaning agent changeover	3	4.763-950.0	300 bar	40					<input type="checkbox"/>
<b>Inaktiv</b>									
Dirt blaster with changeover to fan jet	4	4.763-956.0	300 bar	40					<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# ACCESSORIES FOR HDS 6/14 CX

## 1.169-220.0



		Order No.	Flow rate				Price	Description	
<b>Cup foam lance</b>									
Cup foam lance	1	6.394-668.0	1200 l/h					Short, handy foam lance with adjustable spray angle with 1 litre detergent tank. Ideal for cleaning cars due to its compact design.	<input type="checkbox"/>
1-litre cleaning agent container for foam lance	2	6.414-954.0							<input type="checkbox"/>
<b>Inno Foam Kit</b>									
Inno Foam Set	3	2.640-692.0						High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.	<input type="checkbox"/>
<b>Easy Foam Set</b>									
Easy Foam Set	4	2.640-693.0						HP foam system for use with HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.	<input type="checkbox"/>
<b>Nozzle kits for Inno/Easy Foam Set</b>									
Nozzle kit 055 for Inno / Easy Set 500-600 l/h	5	2.640-870.0	500-600 l/h					Optimal adaptation to different machine outputs for economic use.	<input type="checkbox"/>
<b>Foam nozzle mounting kit</b>									
Foam nozzle attachment kit	6	2.637-926.0						Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# ACCESSORIES FOR HDS 6/14 CX

## 1.169-220.0



		Order No.	Length				Price	Description	
<b>Automatic, self-winding hose reels</b>									
ABS automatic hose drum HDS C	1	2.643-052.0	20 m						<input type="checkbox"/>
ABS holder, automatic hose drum HDS C	2	2.643-181.0							<input type="checkbox"/>
Automatic hose reel, powder-coated steel / plastic	3	6.392-975.0	20 m					Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.	<input type="checkbox"/>
Automatic stainless steel / synthetic material hose drum	4	6.392-965.0	20 m					Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.	<input type="checkbox"/>
Automatic hose reel, coated	5	2.639-919.0	20 m					Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.	<input type="checkbox"/>
Powder-coated swivel holder	6	2.639-931.0						Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.	<input type="checkbox"/>
Automatic hose reel, stainless steel, includes swivel holder	7	6.391-421.0	20 m					Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	<input type="checkbox"/>
ABS automatic stainless steel hose drum	8	2.641-866.0	20 m					High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrosion-resistant, watertight capsuled sprong drive. Connection for HP hoses with nipple.	<input type="checkbox"/>
ABS pivoting stainless steel wall bracket	9	2.641-867.0						Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.



# ACCESSORIES FOR HDS 6/14 CX

## 1.169-220.0



		Order No.	Length	Diameter		Price	Description	
<b>Starting current limiter</b>								
Starting current limiter	1	2.637-495.0					Reduces starting current in single-phase supply and protects line fuse.	<input type="checkbox"/>
<b>Geka coupling</b>								
Geka connector with hose barb, R 1/2"	2	6.388-461.0					with hose liner	<input type="checkbox"/>
Geka connector with hose barb, R 3/4"	3	6.388-455.0						<input type="checkbox"/>
Geka connector with hose barb, R 1"	4	6.388-465.0						<input type="checkbox"/>
Hose coupling	5	6.388-458.0					with female thread	<input type="checkbox"/>
<b>Suction filter</b>								
Water suction filter	6	6.414-956.0						<input type="checkbox"/>
Suction filter with check valve	7	4.730-012.0					Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	<input type="checkbox"/>
<b>Water fine filter</b>								
Water fine filter, with adapter	8	4.730-102.0					Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1".	<input type="checkbox"/>
Water fine filter, 100 µm, R 1"	9	2.638-270.0					Fine-mesh water filter, 100 µm, max. temperature 60°C. Connects to high-pressure cleaner. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connector 1".	<input type="checkbox"/>
<b>Water supply hose</b>								
Water supply hose	10	4.440-038.0	7.5 m				NW 13 R1" / R 3/4", up to 30 °C	<input type="checkbox"/>
	11	4.440-207.0	7.5 m				NW 19 R1" / R 3/4", up to 85 °C, for pick-up	<input type="checkbox"/>
	12	4.440-270.0	7.5 m				NW 19 R1" / R1", up to 85 °C	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# ACCESSORIES FOR HDS 6/14 CX

## 1.169-220.0



1



2-3

		Order No.	Flow rate				Price	Description	
<b>Push-on washing brush</b>									
Push-on washing brush	1	4.762-016.0						Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 x 1.6.	<input type="checkbox"/>
<b>Rotating washing brush</b>									
Rotating wash brush for < 800 l/h machines, natural hair bristles	2	4.762-560.0	500-800 l/h						<input type="checkbox"/>
Rotating wash brush for < 800 l/h machines, nylon bristles	3	4.762-561.0	500-800 l/h					The rotating wash brush gently removes fine dust and grime from all surfaces. Heat-resistant up to 60°C. (M 18 x 1.5, replaceable brush insert).	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.